



Technical Data Sheet

P-SHIELD®

PS-2757

Product Description:


P-SHIELD® PS-2757 is an electrically conductive acrylic pressure sensitive adhesive that offers low contact resistance, superior adhesion to a wide variety of substrates and conductivity in the x, y, and z-plane.

Construction / Properties:

Property	Value	Test Method
Thickness (excluding liners)	0.015 mm $\pm$ 0.01 mm	QSP-726
Color	Gray	Visual
Surface Resistivity	<0.15 Ω /sq	QSP-741
Z-Axis Resistivity	<0.15 Ω /in ²	QSP-741
Acrylic Adhesion	>600 g/25mm	QSP-722
Shielding Effectiveness (30 MHz - 1.5 GHz)	70 - 100 dB	ASTM D4935
Recommended Application Specification	2 kg/square inch for 2 seconds	--
Continuous Use Conditions	-10 - 80 C	QSP-754

Features:

- Superior Converting Properties
- Excellent Shielding Effectiveness
- Excellent Conformability
- Excellent Tack
- Excellent Adhesion to Low Surface Energy Substrates
- RoHS and HF Compliant



Specific tests should be performed by the end user to determine the product stability for the particular application.

For Additional Information:

E-mail: sales@polymerscience.com
Toll Free: +1 888.533.7004
Web: www.polymerscience.com
Revision: 061625